PIP Linac, Laser Notch and TRACEWIN

J.-P. Carneiro

Laser Notch Review / FNAL


05-AUG-2014

Outline (and Conclusion)


- Actual TRACEWIN "start-to-end" model of the PIP linac (from the Ion Source to the Booster). MEBT quotes checked carefully with DJ.
- \rightarrow In the actual "s2e" model of the TRACEWIN model, 60 mA / 100k distribution is generated at the ion source and 41949 particles reach the booster. 25.169 mA at booster from TW. Close to what is measured on the linac ("low to mid 40% transmission")
- Fernanda requested a new set of simulation to be performed to check the sensitivity of the linac to a new MEBT configuration (to accommodate for the laser notch)
- → First MEBT doublet pushed 12.5 mm closer to the MEBT buncher.
- With the new MEBT configuration, 40209 particles reach the booster without any rematching. 24.125 mA at booster. Additional loss of about 4.15 % from actual configuration.
- After a "light" rematching (lowering the MEBT quads by few percent) 41497 reach booster. 24.9 mA at booster. Additional loss of about 1% from actual configuration.

July-2014 TRACEWIN model of the PIP linac

PIP LEBT DISTANCES (TRACEWIN Model)




PIP MEBT DISTANCES (TRACEWIN Model)




At the Booster Region (TRACEWIN Model)

Where does the TW model ends ?: 6.145 meters downsteam Q17 (see below)





RMS Size X and Y along the PIP Linac (From TRACEWIN, July 2014 lattice)

100k / 60 mA at Ion Source. 41949 at Booster.




Losses along the PIP Linac (From TRACEWIN, July 2014 lattice) 100k / 60 mA at Ion Source. 41949 at Booster.






MEBT modification for laser notch installation

Laser Notch Implementation on the PIP MEBT (First doublet pushed downstream by 12.5 mm)




Losses along the PIP Linac (From TRACEWIN, July 2014 lattice) 100k / 60 mA at Ion Source. 40209 at Booster.




Losses along the PIP Linac (From TRACEWIN, New MEBT Configuration, No Rematching) 100k / 60 mA at Ion Source. 40209 at Booster.


TraceWin - CEA/DSM/Irfu/SACM




Losses along the PIP Linac (From TRACEWIN, New MEBT Configuration, After Rematching) First MEBT doublet lowered by ~4%. Second MEBT Doublet by about 2%. 100k / 60 mA at Ion Source. 41453 at Booster.




Beam Sizes at the laser notch Installation (3 locations)



1/ 60 mm + 12.7 mm from RFQ (1/2 inch)




4D (X-X'-Y-Y')



Sigma_Phase [rms] = 28.8908 deg Sigma_Energy [rms] = 0.0470 MeV $E [rms] = 0.1485924931 (Pi.mm.mrad)^{2} [Norm.]$ Sigma_X [rms] = 1.4089 mm Sigma_Y [rms] = 1.7062 mm

3/ 60 mm + 38.1 mm from RFQ (1.5 inches)



Sigma_X [rms] = 1.5474 mm Sigma_Y [rms] = 1.9294 mm